

Fence post PCK with cover strip, section 60 x 40 x 2 mm



Fence post PCK with cover strip

The PCK fence post system ensures in combination with our double wire panels a very easy assembly and exceptional security. The synthetic clips of this fence post system also reduces noise. With the screw connections of all wire panel meshes and the theft-proof aluminium cover cap, the PCK fence post is extremely robust and vandal-proof.

Technical specifications:

Rectangular section: 60 x 40 x 2 mm
Cover strip: 40 x 5 mm
Underground depth of post: 400 - 600 mm

Height: from 630, 830, ... up to 2,340 mm
Screw connection: stainless steel socket screw 8 x 40 mm,

wrench size 5.5 mm (ISO 7380)

Noise reduction: weatherproof synthetic clip with steel insert
Cap: theft-proof aluminium cap in colour of post
Obviously, special sizes, executions and lengths are available at request.

Possible surface treatments:

- Hot-dip galvanised according to EN ISO 1461
- Hot-dip galvanised according to EN ISO 1461 with additional polyester powder coating
- Sendzimir galvanised with additional polyester powder coating
- Standard colours: RAL 6005, 6009, 7016 & 9005, other colours available at request

- Suited for the assembly of all double wire panels
- Durable
- Can be delivered with several floor plates for securing the posts
- Available with several types of anti-climb accessories
- All RAL colours available
- Easy and fast assembly with our double wire panels
- Variable height gradation for uneven grounds
- Can be easily combined with our doors and gates
- Very good price/quality ratio

Weight table		
Height	Galvanised	Galvanised + coated
630 mm	4.1 kg	4.2 kg
830 mm	5.3 kg	5.4 kg
1,030 mm	6.6 kg	6.7 kg
1,230 mm	7.5 kg	7.7 kg
1,430 mm	8.4 kg	8.6 kg
1,630 mm	9.4 kg	9.6 kg
1,830 mm	10.3 kg	10.5 kg
2,030 mm	11.3 kg	11.5 kg
2,230 mm	12.2 kg	12.5 kg
2,430 mm	13.1 kg	13.4 kg